

THREE DIVER PORTABLE AIR PANEL SY-3DAP-BP-DO23-X-XXX



PART NUMBER : SY-3DAP-BP-D023-R-3DV

IMCA D023	DESIGN for Surface Oriented (Air) Diving Systems
IMCA D018	Code of Practice for The Initial and Periodic Examination, Testing and Certification of Diving Plant and Equipment




THREE DIVER PORTABLE AIR PANEL SY-3DAP-BP-DO23-X-XXX


Information Three Diver Panel

Case	Model 1780, Black, Interior (41.1" L x 21.5" W x 14.9" H), with wheels and handle, water, rust and dust proof), Pelican USA Exterior dimensions: 114 x 64.3 x 41.9 cm (44.9" x 25.3" x 16.5") Interior dimensions: 104.4 x 54.7 x 37.8 cm (41.1" x 21.5" x 14.9") Weight including panel : 76kg (167.5lbs)
------	--

Sr.	Description
1	Marine grade aluminium, non-rust fascia in Matt grey finish (other colors available)
2	All engraved lines with each valve/fitting/regulator clearly marked
3	SS etched side plate for all the external fittings

1 x 0-230 fsw/70 msw Depth gauge, 6", 0.25 % accuracy, mirror scale, with calibration point , Diver 1, Color coded Green 

1 x 0-230 fsw/70 msw Depth gauge, 6", 0.25 % accuracy, mirror scale, with calibration point, Diver 2, Color coded Yellow 

1 x 0-230 fsw/70 msw Depth gauge, 6", 0.25 % accuracy, mirror scale, with calibration point, Diver 3, Color coded Red 
--

Air Supplies	HP - 3 independent supplies, one per diver, LP - 3 independent supplies, one per diver
Communication	Amron 2830A-11 Three diver radio with AC/DC power supply
Regulator	1 x per diver, suitable for breathing air, Inlet : 6000 psi, outlet : 400 psi
Relief valves	0-250 psi on regulated diver supply line, 100 psi on pneumo gauges

Air supply ports:

Option 1	All fittings provided from behind the panel for inlets and outlets
Calibration	Inbuilt calibration points for pneumo gauges

Optional :

CCTV	Can be provided for all three divers or two divers
Monitor	TFT 8.5" (splitter will be provided if both diver CCTV options are required)
Surface control unit	All touch button controls with backlight for low visibility operations, video and light control
Primary recording	upto 256GB SD card, one per diver
Secondary back up recording	1 TB backup hard drive to record all diver video simultaneously

Sr.	Part Number	Description	Qty
1	SY-PRO-O2	Oxygen analyzers with high low alarm (one per diver)	3
2	SY-VFA-BV-23	Flowmeters (per analyzer)	3
3A	SY-873-400	Option 1 Aqua Environment high pressure Regulator w/gauges	3
3B	SY-44-1315-2081-005	Option 2 Tescom high pressure regulator	3
4	SY-FLR-DS	Flow Restrictor (one per diver)	3
5	SY-PG-A-2.5-5000	High pressure gauges (incoming air supply) 0-5000 psi (HP1)	3
6	SY-PG-A-2.5-500	Low pressure gauge (regulated air supply) 0-500 psi	3
7	SY-PG-A-2.5-500	Low pressure gauge (downstream for umbilical supply pressure)	3
8	All air supply lines (inlet and outlet) are color coded per diver		
9	Diver 1 - Independent high pressure line Diver 2 - Independent high pressure line Diver 3 - Independent high pressure line		

THREE DIVER PORTABLE AIR PANEL SY-3DAP-BP-DO23-X-XXX


Sr.	Description
11	Diver 1 – Independent low pressure line Diver 2 – Independent low pressure line Diver 3 – Independent low pressure line
12	All tubing used will be stainless steel high pressure
13	All valves for incoming air supplies will be brass/ss, high pressure
14	All valves for regulated supplies will be brass/ss, high pressure

DIVE PANEL COMMUNICATION

Sr.	Part Number	Description	Qty
1	2830A-11	Amron 3 diver radio with ac/dc power	1
2	2405-28	Push to talk microphone	1

DIVE PANEL COMMUNICATION

Sr.	Part Number	Description	Qty
1	SY-DIVERVISION SERIES	Diver 1/Diver 2 / Diver 3 , surface control unit, Synergy/Outland Technology	3
2	SY-MON-8.5-TFT	Diver 1/Diver 2 / Diver 3 , 8.5"waterproof TFT monitor	3
3	SY-DVR-256GB-SD	Primary Recorder, 256GB SD card (individual DVR per diver)	3
4	SY-DVR-1TB-HD	Backup recorder (black box) 1 TB hard drive (simultaneous recording of all dives) , USB out for recording to USB sticks, HDMI out for mirror image to be displayed remotely via HDMI cables	1



SY-2830A-11 AMCOM III THREE-DIVER RECHARGEABLE BASIC PORTABLE COMMUNICATOR

SY-2830A-11 AMCOM III THREE-DIVER RECHARGEABLE PORTABLE COMMUNICATOR WITH OUTDOOR AC POWER MODULE AND INTERNATIONAL LOCKING POWER CORD



NEWLY DESIGNED ENHANCEMENTS:

High Audio Fidelity

Ultra-low noise circuit combined with noise suppression circuitry produces crystal clear speech. Automatic gain adjustment

will guard audio signal from distortion, enhance speaker protection and audio quality. Increases band width 47%.

Extended Battery Operation Time

Audio amplifier card deploys the state-of-the-art Class-D digital audio power amplifier. Has very low power dissipation, produces less heat, and extends battery life up to 32%.

Flexible Gain Settings

The audio amplifier card has adjustable gain settings to accommodate different communication applications and environments.

Ultra-Low Electromagnetic Interference (EMI)

EMI is achieved through spread-spectrum and de-phase control techniques providing for optimum integration with diving systems.

Outdoor Rated AC Power Module

Weather resistant, IP65 rated AC power entry module accommodates country specific AC power cords.

Country Specific V-Lock AC Power Cord

At time of order, simply choose the IP54 rated Locking AC power cord you need.

FEATURES:

- Separate channels and volume controls for each diver and tender to accommodate individual earphone and microphone adjustments, equipment variations and individual comfort levels.
- Divers' umbilicals can be set to 4-wire mode (full duplex) or 2-wire mode (push-to-talk) or any combination of the two modes for any diver.
- Ability to use both dynamic and pre-amplified diver microphones with a unique circuit that detects microphone type and automatically adjusts volume levels.
- Weatherproof push-to-talk microphone for better voice intelligibility topside. For optimum clarity, see Tech Note (below) for other recommended equipment.
- Internal charger allows for simultaneous charging and operation of the unit while protecting the rechargeable battery from being over-charged. Automatically supplies power to the audio amplifier when AC power is disconnected to allow for continued operation.

SY-2830A-11 AMCOM III THREE-DIVER RECHARGEABLE BASIC PORTABLE COMMUNICATOR

SPECIFICATIONS:

- Input Impedance (Each Input): 250 Ohms
- Frequency Response: 300 - 10000 Hz
- Common Mode Rejection: 40 dB Minimum
- Current Drain Maximum Full Volume: 3 Amps
- Minimum Quiescent: 0.190 Amps
- Output Impedance: 4 Ohm
- Power Supply Voltage: 12 VDC Nominal (9 Volts Minimum - 16 Volts Maximum)
- AC Power Operating Range: 90-264 VAC, 50-60 Hz
- Sensitivity (Input): 0.5 mV
- Output Power (RMS @ 4 Ohm Load, 12 VDC): 10 Watts Audio
- Battery Life: 41 hours
- Dimensions: 10 in. H x 9 in. W x 14.5 in. L (25.4 cm x 22.9 cm x 36.8 cm)
- Weight: 17.05 Lbs. (7.73 Kg)

INCLUDED WITH COMMUNICATOR:

SY-2830A-11 AMCOM III Two-Diver Rechargeable Basic Portable Communicator with Outdoor Power Module and International Locking Power Cord includes:

- (1) SY-2405-28 Amron Hand-Held Push-to-Talk Microphone
- (1) SY-2890-05 Amron 12 VDC Sealed Lead Acid Gel-Cell Rechargeable Battery with Slide terminals
- (1) SY-283XA-UM Amron Three-Diver Portable Communicator User Manual

AVAILABLE OPTIONS:

- SY-2460SM-28 Amron Single Muff Operator Headset with Boom Mic and Dual Banana Plugs
- SY-2401-28 Amron Deluxe Headset with Boom Mic
- SY-2822-28 Amron Remote Walk-and-Talk (4-wire mode)
- SY-2821-28 Amron Remote Walk-and-Talk (2-wire mode)

TECH NOTE:

All communicators will inherently transfer topside noise to the divers when the tender speaks directly into the communicator's panel speaker. To eliminate background noise at the surface, use the 2405-28 Push-to-Talk Microphone, included with this model. For optimum communications, we recommend purchasing the 2401-28 Deluxe Headset with Boom Mic, topside. For tender mobility, use the 2401-28 Deluxe Headset with Boom Mic along with the 2822-28 Remote Walk-and-Talk (4-wire mode) or the 2821-28 Remote Walk-and-Talk (2-wire mode). For wireless tender communications, order the 2830A-03 Three-Diver Deluxe Portable Communicator with Wireless Tender.

THREE DIVER PORTABLE AIR PANEL SY-3DAP-BP-DO23-X-XXX

ORDERING INFORMATION

Sr.	Part Number	Description
1	SY-3DAP-BP-D023-R-3DV	THREE DIVER PORTABLE AIR PANEL, WITH 1 X AMRON 3 DIVER AIR RADIO, D1 / D2 / D3 VIDEO SYSTEMS

BESPOKE DESIGNS – ANY CONFIGURATION AS PER CLIENT REQUIREMENT



THREE DIVER PORTABLE AIR PANEL SY-3DAP-BP-DO23-X-XXX

Contact us



29th Street, Amman Road, Behind Al Huraiz Est. For Industry,
Al Qusais, Industrial Area – 1,
Dubai, United Arab Emirates



Tel : 009714 2580533 



Fax : 042516664 



UAE : 00971505648178 



UK : 00447951966260 



Website : www.synergiequipment.com



Email : ram@synergiequipment.com



For Sale : info@synergiequipment.com

