



SYNERGY

INNOVATIVE DIVING EQUIPMENT TRADING LLC

INSPIRING • ENGINEERING • INNOVATION

UAE • UK • INDIA • AZERBAIJAN



SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)



Shipping containers make ideal structures to install diving equipment inside, due to their qualities of strength, security, longevity and probability.

Synergy stock a limited quantity of Dnv Offshore Containers for conversion and sales.

We have an in house fabrication team who can design and built any containerized solutions for all of your diving equipment and storage needs. Our Cad team can design the equipment that the client needs to be installed into the containers (10ft or 20ft, iso or dnv). We also do iso to dnv pad eye conversions, insulation of containers, climate control (standard and zone 2)

Special conversions for storage of your diving equipment, generators, welding equipment and stores

We are specialized in reinstallation of your diving equipment from old containers to new containers, from your old iso containers to present day DNV offshore containers suitable for offshore use.

Synergy can also recertify your diving equipment once installed in the containers to Imca standards.



BRAND NEW DNV 20FT CONTAINERS

SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)





INSPIRING • ENGINEERING • INNOVATION

UAE • UK • INDIA • AZERBAIJAN

SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)



SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)





SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)





SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)



SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)





SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)





SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)



SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)





SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)



SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)





SYNERGY
INNOVATIVE DIVING EQUIPMENT TRADING LLC

INSPIRING • ENGINEERING • INNOVATION

UAE • UK • INDIA • AZERBAIJAN

SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)



10FT DIVE CONTROL STATION WITH THREE DIVER PANEL SY-10FTDC-XX-XXX



Iso container – Standard 10ft x 8ft with manufacturer certificate
Fully insulated with fire retardant sandwich panel, PU 35kg/m3
Climate Control – Split air conditioner installed, 220v, 50 / 60 hz, 1.5 tons
Shelf provided above quad to store stretcher and dmac kit
1 x side door next for easy access to Quad Cylinders
1 x main door for entrance to container and access to dive panel for supervisor, with view windows provided on both doors (wire glass for added protection)
1 x Window, sliding, wire glass, big, for view outside the container
2 x windows, fixed, wire glass, on main container doors, for view outside the container
1 x 3 pin Male main Electrical inlet connection for power supply to container

10FT DIVE CONTROL STATION WITH THREE DIVER PANEL SY-10FTDC-XX-XXX



DNV Container Specifications.

DNV Offshore container 2.7-1 – 10ft x 8ft with manufacturer certificate
Fully insulated with fire retardant sandwich panel, PU 35kg/m3
Climate Control – Split air conditioner installed, 220v, 50 / 60 hz, 1.5 tons
Shelf provided above quad to store stretcher and dmac kit
1 x side door next for easy access to Quad Cylinders
1 x main door for entrance to container and access to dive panel for supervisor, with view windows provided on both doors (wire glass for added protection)
1 x Window, sliding, wire glass, big, for view outside the container
2 x windows, fixed, wire glass, on main container doors, for view outside the container
1 x 3 pin Male main Electrical inlet connection for power supply to container

OPTION 1 – DNV 2.7-1 EN12079 CERTIFIED OFFSHORE CONTAINER



Container	Specifications
Internal dimensions	L5.896 x B2.346 x H2.352 mm
External dimensions	L6.058 x B2.438 x H2.591 mm
Door opening	B2.338 x H2.253 mm
Volume	32,54 m ³ ,
Tare weight	970 kgs ¹³ ,
Max payload	530 kgs ¹⁶ ,
Max cargo weight	500 kgs
Color	Customized painting to client specifications
Certifications	DNV 2.7.1 / EN 12079 / ISO / CSC
Logo	Client logos done on special request

OPTION 2 – ISO CONTAINER



Container	Specifications
Internal dimensions	L5.898 x W2.350 x H2.393 mm
External dimensions	L6.058 x W2.438 x H2.591 mm
Door opening	W2.342 x H2.280 mm
Volume	33,10 m ³
Tare weight	2.150 kgs
Max payload	28.330 kgs
Max cargo weight	30.480 kgs
Color	Customized painting to client specifications
Certifications	CSC certified
Logo	Client logos done on special request



SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)

Outside Length	Outside Height	Outside Width	Internal Length	Internal Height	Internal Width	Door Width	Door Height	Cubic Capacity	Max Gross Weight	Tare Weight
8ft Container Dimensions	2.44m 8ft	2.26m 7ft 6in	2.26m 7ft	2.29m 7ft 6in	2.06m 6ft 6in	2.11m 6ft 11in	2.10m 6ft 11in	1.95m 6ft 5in	9.95m³ 351cf	6,000kg 13,227lbs 950kg 2,094lbs
10ft Container Dimensions	2.99m 10ft	2.59m 8ft 6in	2.44m 8ft	2.84m 9ft 4in	2.39m 7ft 10in	2.35m 7ft 9in	2.34m 7ft 9in	2.28m 7ft 6in	15.95m³ 563cf	10,000kg 22,046lbs 1,000kg 2,204lbs
20ft Container Dimensions	6.06m 20ft	2.60m 8ft 6in	2.44m 8ft	5.9m 19ft 4in	2.39m 7ft 10in	2.35m 7ft 9in	2.34m 7ft 9in	2.28m 7ft 6in	33.2m³ 1,172cf	30,480kg 67,196lbs 2,000kg 4,409lbs
40ft Container Dimensions	12.2m 40ft	2.60m 8ft 6in	2.44m 8ft	12.03m 39ft 5in	2.39m 7ft 10in	2.35m 7ft 9in	2.34m 7ft 9in	2.28m 7ft 6in	67.6m³ 2,387cf	30,480kg 67,196lbs 3,470kg 7,650lbs
20ft Tunnel Dimensions	6.06m 20ft	2.60m 8ft 6in	2.44m 8ft	5.84m 19ft 1in	2.39m 7ft 10in	2.35m 7ft 9in	2.34m 7ft 9in	2.28m 7ft 6in	32.8m³ 1,158cf	30,480kg 67,196lbs 2,180kg 4,806lbs
20ft Open-sider Dimensions	6.06m 20ft	2.60m 8ft 6in	2.44m 8ft	5.9m 19ft 4in	2.30m 7ft 6in	2.29m 7ft 6in	2.22m 7ft 3in	2.19m 7ft 3in	31m³ 1,094cf	30,480kg 67,196lbs 3,170kg 6,988lbs
40ft High Cube Dimensions	12.2m 40ft	2.90m 9ft 6in	2.44m 8ft	12.03m 39ft 5in	2.69m 8ft 10in	2.35m 7ft 9in	2.34m 7ft 8in	2.58m 8ft 6in	76.4m³ 2,698cf	30,480kg 67,196lbs 3,660kg 8,068lbs
20ft Open-top Dimensions	6.06m 20ft	2.90m 9ft 6in	2.44m 8ft	5.96m 19ft 4in	2.28m 7ft 6in	2.35m 7ft 9in	2.34m 7ft 9in	2.28m 7ft 6in	33m³ 1,165cf	30,480kg 67,196lbs 3,000kg 6,613lbs
40ft Open-top Dimensions	12.2m 40ft	2.60m 8ft 6in	2.44m 8ft	12.03m 39ft 5in	2.39m 7ft 10in	2.35m 7ft 9in	2.34m 7ft 9in	2.28m 7ft 6in	66.8m³ 2,358cf	32,500kg 71,650lbs 4,050kg 8,928lbs
40ft Tunnel Dimensions	12.2m 40ft	2.60m 8ft 6in	2.44m 8ft	11.98m 39ft 4in	2.39m 7ft 10in	2.35m 7ft 9in	2.34m 7ft 9in	2.28m 7ft 6in	67.4m³ 381cf	30,480kg 67,196lbs 3,680kg 8,113lbs
40ft High Cube Open Sider Dimensions	12.2m 40ft	2.90m 9ft 6in	2.44m 8ft	12.03m 39ft 5in	2.46m 8ft 1in	2.28m 7ft 6in	2.22m 7ft 3in	2.35m 7ft 9in	67.72m³ 2,391cf	24,000kg 52,910lbs 5,920kg 13,051lbs
20ft High Cube Dimensions	6.06m 20ft	2.90m 9ft 6in	2.44m 8ft	5.96m 19ft 4in	2.69m 8ft 10in	2.35m 7ft 9in	2.34m 7ft 9in	2.58m 8ft 6in	37.4m³ 1,320cf	30,480kg 67,196lbs 2,100kg 4,629lbs

BESPOKE DESIGNS - ANY CONFIGURATION AS PER CLIENT REQUIREMENT



SYNERGY INFRASTRUCTURE





SYNERGY

INNOVATIVE DIVING EQUIPMENT TRADING LLC

INSPIRING • ENGINEERING • INNOVATION

UAE • UK • INDIA • AZERBAIJAN



SYNERGY -CONTAINER & CONVERSIONS 10FT, 20 FT (ISO & DNV)

Contact us

 29th Street, Amman Road, Behind Al Huraiz Est. For Industry,
Al Qusais, Industrial Area - 1,
Dubai, United Arab Emirates

 Tel : 009714 2580533 
 Fax : 009714 2580534 
 UAE : 00971505648178 
 UK : 00447951966260 

 Website : www.synergiequipment.com
 Email : ram@synergiequipment.com
 For Sale : info@synergiequipment.com

